

# BETON



## ACRYLIC SEALER FOR CONCRETE AND POROUS FLOORS

- Suitable for porous floors (ex. terracotta floors etc..)
- Anti-dust effect and anti-stain effect
- Resistant to heavy traffic

Acrylic sealer specially designed for very porous floors. Anti-dust effect and resistant to heavy traffic. Excellent anti-stain effect.

### ? HOW TO USE

After carefully removing wax and any saltpetre deposits, apply two coats of sealer using the special wax applicator (the first coat should be diluted with 50% water to make impregnating easier). Leave to dry approximately 45 min. between one coat and the next.

### 📖 DILUTION

Ready to use.

### 🔍 TECHNICAL DATA

**ASPECT:** Opaque liquid

**COLOR:** Creamy white

**PERFUME:** Technical

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
7,7 ± 0,5		1.018			20,5 - 21,5

### ⚠ WARNINGS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contents METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

### 📝 NOTES

Check that the sealer adheres to concrete floors and do not apply BETON at temperatures below 10° C. Keep away from freezing. PRODUCT FOR PROFESSIONAL USE ONLY. SAFETY DATA SHEET AVAILABLE FOR PROFESSIONAL USERS.

## BETON

### PACKAGING

Code	Size	Quantity	Pallet
3822	kg 5	4	9x4=36