

# METEOR MATT



## HIGH RESISTANCE, LOW MAINTENANCE ANTI-SLIP SATIN EFFECT ACRYLIC EMULSION

- Anti-slip effect tested by UL laboratories
- Matt effect
- Reduces frequency of maintenance and costs



Emulsion formulated with an exclusive mixture of polymers and waxes for a special satin effect. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

### HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance. Recommended maintenance: AZZURRO UL for wet maintenance; RAPID UHS UL for spray method.

### DILUTION

Ready to use

### TECHNICAL DATA

**ASPECT:** Opaque liquid

**COLOR:** Creamy white

**PERFUME:** Floral

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,5 ± 0,5	18,5 ± 1	1.023			14,3 - 15,3

### WARNINGS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contents METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

### NOTES

Protective wax for floors. Do not apply METEOR MATT at temperatures below 10° C. Keep away from freezing. PRODUCT FOR PROFESSIONAL USE ONLY. SAFETY DATA SHEET AVAILABLE FOR PROFESSIONAL USERS.

## METEOR MATT

### PACKAGING

Code	Size	Quantity	Pallet
4020	kg 5	4	9x4=36