

METEOR PARQUET



ANTI-SLIP SELF-POLISHING EMULSION FOR TREATED AND UNTREATED PARQUET

- Anti-slip effect tested by UL laboratories
- Very high level shine
- Excellent resistance to traffic



Formulated with a mixture of polymers and waxes specifically created for the porosity of wood floors. Guarantees effective protection and restores the original level of shine. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply one or two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance.



METEOR PARQUET

DILUTION

Ready to use.

FEATURES

Product yields (m²/lt):

Operation category	Conc.%	Product yield (m ² /lt)	Notes
WOOD FLOOR TREATING	100%	15	2 coats

Volume (lt) of pure product diluted according to suggested dilutions.

TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Yellow

PERFUME: Honey

COV/VOC: 0,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,5 ± 0,5		1.025			13 ± 1

WARNINGS

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Dispose of contents/container in accordance with applicable regulations. Contains ZINC AMMONIA CARBONATE COMPLEX, METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction.

NOTES

Protective wax for floors. Do not apply METEOR PARQUET at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product.

Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet.

Do not pour the product down the drain. Do not rinse the container before disposal. Thoroughly clean tools and equipment after use to avoid microplastic release. Dispose of the container according to local waste regulations.

Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

METEOR PARQUET

PACKAGING

Code	Size	Quantity	Pallet
4155	Kg 5	4	9x4=36